

1 [0008] Furthermore, weak elastic lashes are more readily worn or damaged than strong
2 lashes, and more quickly lose their swatting effectiveness. The typical rubber composition
3 used in commercially available rubber bands is subject to environmental degradation which
4 reduces the resiliency or stiffness of the bands, and the effectiveness thereof.

5 [0009] In view of these competing affects it is not practical to optimize elastic lash selection
6 by merely choosing a band length and cross section for the specific size of the intended rod.
7 And, custom made bands merely add to the cost of the swatter, and reduce the convenience
8 thereof.

9 [0010] Accordingly, it is desired to provide an insect swatter requiring reduced skill for its
10 use, reducing stains from the successful swatting of the insect, and including a simple and
11 effective elastic lash.

12

13

SUMMARY OF THE INVENTION

14

15 [0011] An insect swatter includes an elongate rod with an elastic lash fixedly joined to a
16 distal end thereof. The lash includes a pair of annular bands knotted together for being
17 stretched from the rod distal end to adjacent a proximal end of the rod so that release of the
18 lash results in spontaneous contraction thereof for swatting the insect. In an exemplary
19 embodiment, the swatter is in the form of a pistol, with the lash extending from the distal end
20 of the rod to a latch operated by a trigger. Aiming the rod toward the insect and pulling the
21 trigger releases the lash for swatting the insect.

22

23

BRIEF DESCRIPTION OF THE DRAWINGS

24

25 [0012] The invention, in accordance with preferred and exemplary embodiments, together
26 with further objects and advantages thereof, is more particularly described in the following
27 detailed description taken in conjunction with the accompanying drawings in which:

28 [0013] Figure 1 is an elevational view of a hand-held insect swatter in accordance with one
29 embodiment of the present invention.

30 [0014] Figure 2 is an elevational, partly sectional enlarged view of the insect swatter

-3-

1 illustrated in Figure 1 showing a trigger and cooperating latch in cocked positions.

2 [0015] Figure 3 is an enlarged, partly sectional view of the insect swatter illustrated in
3 Figure 2 showing a trigger and cooperating latch in fired positions.

4 [0016] Figure 4 is a top, partly sectional view of the insect swatter illustrated in Figure 2 and
5 taken generally along line 4-4.

6 [0017] Figure 5 is an isometric view of a duplex lash in accordance with an exemplary
7 embodiment.

8 [0018] Figure 6 is a top view of the insect swatter illustrated in Figure 1 having the duplex
9 lash of Figure 5 installed therein.

10

11 DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

12

13 [0019] Illustrated in Figure 1 is an exemplary embodiment of an insect swatter 10 in the
14 exemplary form of a pistol, although in other embodiments it may be in the form of a rifle or
15 other suitable configurations. The swatter 10 includes an elongate rod 12 which may be solid
16 as illustrated, or hollow if desired, and may have any suitable cross section such as circular for
17 example.

18 [0020] The rod 12 has a proximal end 12a for being hand-held, and in the exemplary
19 embodiment illustrated in Figure 1 a gun-type handgrip 14, in the exemplary form of a pistol
20 handgrip, is suitably fixedly joined to the rod proximal end 12a. In alternate embodiments, the
21 handgrip 14 could be a rifle handgrip with a cooperating shoulder stock for example. The
22 handgrip 14 provides a convenient manner for hand holding the elongate rod 12 and aiming it
23 toward an insect 16, such as a fly for example.

24 [0021] The rod 12 has a distal end 12b, opposite to the proximal end 12a, which is aimed
25 during operation at or toward the insect 16. An elastic lash 18 in the exemplary form of a
26 conventional annular rubber band has a proximal end 18a fixedly joined to the rod distal end
27 12b which retains the lash 18 to the rod 12. The lash 18 has an opposite, distal end 18b which
28 is used for swatting or killing the insect 16.

29 [0022] As shown in Figure 1, the lash 18 is preferably so sized or so dimensioned for being
30 stretched from the rod distal end 12b to adjacent the rod proximal end 12a so that release of

1 the lash distal end 18b spontaneously contracts or "fires" the lash 18 for swatting or whipping
2 the lash distal end 18b against the insect 16.

3 [0023] An exemplary method of using the swatter 10 includes manually stretching the lash
4 18 by pulling the distal end 18b thereof generally parallel to the rod 12 and adjacent to the rod
5 proximal end 12a which stores energy in the lash 18. This is shown in phantom line in Figure
6 1 and in solid line in Figure 2. By aiming the rod distal end 12b at the insect 16 and within
7 reach or striking range R of the whipping lash 18, and then releasing the lash distal end 18b,
8 the lash 18 spontaneously contracts for swatting the lash distal end 18b against the insect 16,
9 with the kinetic energy released by the lash 18 being sufficient for killing or severely maiming
10 the insect 16.

11 [0024] In its simplest form, the rod 12 and the attached lash 18 form a whip. The rod 12 is
12 used for manually aiming the swatter 10 at the insect 16 so that the energy stored in the
13 stretched lash 18 causes the lash 18 to accelerate from the rod proximal end 12a, generally
14 parallel along the rod 12 toward the rod distal end 12b, and continue to travel in the same
15 direction away from the rod distal end 12b for impacting the insect 16.

16 [0025] The whipping action of the lash 18 is shown in three positions in Figure 1 and will
17 carry the lash 18 along the line-of-sight formed by the rod 12 aimed at the insect 16 for
18 allowing easy and accurate swatting thereof. As long as the rod distal end 12b is positioned
19 within the whipping range R of the lash 18, the insect 16 may be effectively swatted.

20 [0026] The lash 18, like a whip cord, is completely flexible, not rigid, but unlike a whip
21 cord, it is also elastically stretchable. It may have any suitable cord-like configuration, such as
22 the rubber band disclosed in the preferred embodiment. In this way, energy may be
23 conveniently stored in the stretched lash 18 by stretching it in one direction, and then the
24 energy is released which carries the lash 18 along the line-of-sight in the direction opposite to
25 the stretching direction thereof to accurately hit the insect 16. The striking energy includes the
26 energy stored in the stretched lash 18, as well as any additional energy due to the whipping
27 effect. The lash 18 is therefore not an expendable, one-shot projectile, but remains with the
28 rod 12 for repeated use.

29 [0027] Since the lash 18 itself stores the energy used for moving the lash 18, it is relatively
30 easy to use and does not require the fast hand action required of a typical fly swatter.

1 Whipping of the lash 18 is spontaneous and occurs within a fraction of a second for quickly
2 swatting the insect 16 well before its ability to react thereto. Furthermore, the lash 18 is
3 relatively small as compared to conventional fly swatters, and is less visible by the insect 16
4 compared thereto, and moves less air than a conventional fly swatter which reduces the ability
5 for the insect 16 to sense the striking action of the lash 18.

6 [0028] Yet further, the energy imparted by the whipping lash 18 against the insect 16 is
7 confined to a very small point which in most cases immediately kills the insect 16 with little or
8 no stain therefrom due to the striking thereof.

9 [0029] In its simplest form, the lash 18 may be manually stretched and held at its distal end
10 18b adjacent to the rod proximal end 12a and then manually released for swatting the insect
11 16. However, in order to add additional convenience and accuracy in using the swatter 10, it
12 preferably further includes a latch or hook 20 as shown in more particularity in Figure 2.

13 [0030] The latch 20 may simply be in the form of a straight, smooth bar having an enlarged
14 proximal end 20a through which extends a latch pin 22a for pivotally joining the latch 20 to
15 the handgrip 14 adjacent to the rod 5 proximal end 12a for releasably latching the lash distal
16 end 18b thereto. The latch 20 is joined to the top of the handgrip 14 in a suitable cavity
17 therein.

18 [0031] The latch 20 is shown in Figure 2 in a first or cocked position wherein the latch 20
19 extends generally perpendicularly upwardly from the rod 12, or from its longitudinal
20 centerline axis, for retaining or latching the lash distal end 18b thereto. The latch 20 in its
21 cocked position is preferably inclined slightly rearwardly away from the rod 12 to ensure that
22 the lash distal end 18b does not inadvertently slip therefrom prior to firing.

23 [0032] Means including a trigger 24 are operatively joined to the latch 20 for selectively
24 releasing the latch 20 from its cocked position upon pulling the trigger 24 rearwardly to
25 release the lash distal end 18b for swatting the insect 16 therewith. Shown also in Figure 2 is
26 the trigger 24 having an enlarged proximal end 24a which is pivotally joined to the handgrip
27 14 by a trigger pin 22b extending therethrough so that the trigger 24 may be pivoted between
28 the first or cocked position thereof holding the latch 20 in its cocked position, and a second or
29 fired position illustrated in Figure 3 releasing the latch 20 for being pivoted to its fired position
30 also shown in Figure 3.

1 [0033] In its fired position, the latch 20 is inclined forwardly toward the rod distal end 12b
2 for allowing the lash distal end 18b to slip or slide off the latch 20 as shown in Figure 3 for
3 spontaneously contracting the lash 18 toward the rod distal end 12b. The trigger 24 is
4 operatively joined to the latch 20 by any suitable means for releasing the latch 20 to pivot
5 from its cocked position to its fired position upon pulling of the trigger 24.

6 [0034] In an exemplary embodiment, the latch 20 includes an elongate latch cam 20b which
7 extends generally radially outwardly from the latch proximal end 20a and the latch pin 22a
8 toward the trigger proximal end 24a. And, the trigger 24 includes a complementary, elongate
9 trigger cam 24b extending generally radially outwardly from the trigger proximal end 24a and
10 trigger pin 22b therethrough, with the two cams 20b,24b being engaged in the cocked
11 positions for preventing rotation of the latch 20 as shown in Figure 2.

12 [0035] When the trigger 24 is pulled rearwardly as shown in Figure 3, the trigger cam 24b
13 slides past the latch cam 20 which allows the stretched lash 18 to pull the latch 20 into its fired
14 position by rotating it counterclockwise, which in turn then allows the lash distal end 18b to
15 slip from the latch 20 and be released therefrom. A suitable latch stop pin 22c is joined to the
16 handgrip 14 adjacent to the latch pin 22a for limiting the counterclockwise rotation of the latch
17 20 by abutting the latch cam 20b as shown in Figure 3.

18 [0036] As shown in Figures 2 and 3, a trigger return spring 26 in the exemplary form of a
19 flexible cantilever is operatively joined between the trigger 24 and the handgrip 14, with the
20 spring 26 being positioned for providing a returning force on the trigger 24 to return the
21 trigger 24 to its cocked position upon finger release thereof. In the exemplary embodiment
22 illustrated in Figures 2 and 3, the spring 26 extends integrally from the trigger proximal end
23 24a and generally parallel to the upper portion of the trigger 24 itself, and defines a space
24 therebetween in which is disposed a stationary trigger stop pin 22d which is fixedly joined to
25 the handgrip 14.

26 [0037] In Figure 2, the trigger 24 is in its cocked position with the return spring 26 being
27 disposed on one side of the trigger stop pin 22d in an undeflected position for holding the
28 trigger 24 in its forwardmost position abutting the opposite side of the trigger stop pin 22d.
29 Upon pulling the trigger 24 rearwardly, which is shown in phantom line in Figure 2 and in
30 solid line in Figure 3, the spring 26 elastically flexes against the trigger stop pin 22d as the

1 trigger 24 is pulled rearwardly which allows the cooperating latch and trigger cams 20b, 24b
2 to disengage so that the elastic lash 18 may pivot the latch 20 counterclockwise and be
3 released therefrom. When the trigger 24 is released, the return force provided by the spring 26
4 causes the trigger 24 to rotate clockwise until the trigger 24 abuts the stop pin 22d.

5 [0038] Other conventional types of return springs may be used such as tension or
6 compression springs disposed on suitable sides of the trigger 24 to provide the same returning
7 force if desired.

8 [0039] In the exemplary embodiment illustrated in Figures 2 and 3, the latch 20 preferably
9 also includes a conventional thumbgrip 28 integrally joined thereto and extending rearwardly,
10 generally perpendicularly therefrom for manually returning or cocking the latch 20 to its
11 cocked position. After the lash 18 is fired, the latch 20 rotates counterclockwise until the latch
12 stop pin 22c prevents further rotation thereof. With or without releasing the trigger 24, the
13 thumbgrip 28 may be pressed downwardly for rotating the latch 20 clockwise to return it to its
14 cocked position.

15 [0040] If the trigger 24 is in its released position, cocking of the thumbgrip 28 causes the
16 latch cam 20b to temporarily displace the trigger 24 upon sliding against the underside of the
17 trigger cam 24b. When both the latch 20 and the trigger 24 are returned to their cocked
18 positions, the lash 18 may be reloaded or re-affixed to the latch 20 in preparation for the next
19 shot thereof.

20 [0041] As indicated above, the lash 18 is in the exemplary form of a rubber band, with the
21 lash proximal end 18a forming a first loop as shown in more particularity in Figure 4, and the
22 lash distal end 18b forming an opposite, second loop positionable around the latch 20 as
23 shown in Figures 2-4 for being simply retained or latched thereby.

24 [0042] As shown in Figure 2, the rod distal end 12b preferably includes a keyhole slot 30
25 sized for receiving the lash proximal end loop 18a therethrough for retaining the lash 18 to the
26 rod 12 without allowing unintended disconnection therefrom when the lash 18 is fired. The
27 keyhole slot 30 includes an enlarged cylindrical portion extending laterally through the middle
28 of the rod distal end 12b, and a rectangular portion which faces or is open downwardly. The
29 rectangular portion is preferably narrower than the unstretched cross section of the lash 18 to
30 prevent its passage therethrough, with the cylindrical portion being suitably larger than the

1 undistorted cross section of the lash 18 for loosely fixedly joining the lash 18 to the rod 12.

2 [0043] In order to replace a worn or broken lash 18, the worn lash 18 may be suitably
3 removed from the keyhole slot 30, with the replacement lash 18 being initially manually
4 stretched so that its cross section is narrower than the rectangular portion of the keyhole slot
5 30 for allowing it to be inserted through the rectangular portion and into the cylindrical portion
6 of the keyhole slot 30 wherein it is retained after being unstretched.

7 [0044] As shown in Figure 2, the latch 20 extends upwardly from the handgrip 14 or
8 generally perpendicularly to the longitudinal centerline of the rod 12, and the keyhole slot 30
9 is open downwardly in the direction opposite to the upward extension of the latch 20. In this
10 way, the lash 18 is inclined slightly upwardly from the keyhole slot 30 to the latch 20 when
11 latched thereto which provides good retention of the lash 18 to the latch 20 in its cocked
12 position while also providing good aiming capability along the longitudinal axis of the rod 12.

13 [0045] Accordingly, in order to use the swatter 10, the thumbgrip 28 is cocked to position
14 the latch 20 in its cocked position, with the trigger 24 also being positioned in its cocked
15 position as shown in Figure 2 for example. Stretching of the lash 18 is manually
16 accomplished by the operator or user of the swatter 10 by pulling the lash distal end 18b
17 generally parallel to the rod 12 and adjacent to the rod proximal end 12a for latching the lash
18 distal end loop 18b around the latch 20.

19 [0046] As shown in Figure 1, the handgrip 14 is gripped by the hand 32 of the operator or
20 user to aim the swatter 10 along its rod 12 at the insect 16, with the rod distal end 12b being
21 correspondingly aimed at the insect 16 with the fired lash 18 being within striking range R
22 thereof. Upon pulling the trigger 24, the latch 20 is released and spontaneously contracts or
23 fires for swatting the insect 16 with the lash distal end 18b. The lash 18 may be reloaded and
24 refired as often as desired until the lash 18 wears out or breaks. In that case, the lash 18 is
25 readily replaced.

26 [0047] As shown in Figure 1, the lash 18 has an unstretched free length L1. The rod 12 and
27 cooperating latch 20 have or define a collective cocked length L2 measured linearly between
28 the keyhole slot 30 and the latch 20 in its cocked position. The cocked length L2 is preferably
29 selected for stretching the lash 18 to about its maximum stretched length without breaking
30 thereof to maximize the potential energy therein.

1 [0048] In a preferred embodiment, the cocked length L2 is at least three times the lash
2 unstretched length L1 which not only provides substantial striking energy within the lash 18,
3 but also provides a substantial amount of striking range R which is the distance between the
4 insect 16 and the rod distal end 12b. Of course, the striking range R is at least as large as the
5 lash unstretched length L1, and in actuality it is larger than the unstretched length L1 since the
6 kinetic energy in the striking lash 18 causes the lash 18 to stretch in the opposite direction
7 from the rod 12 toward the insect 16 at which it is aimed.

8 [0049] In an exemplary embodiment of the present invention, the lash 18 may be in the form
9 of a common rubber band having an unstretched length L1 of 17 cm with a 2 mm square cross
10 section. The cocked or stretched length L2 of the lash 18 is about 60 cm which provides a
11 substantial striking range R for the swatter of about 38 cm, which is greater than twice the
12 unstretched length L1.

13 [0050] The swatter 10 may be manufactured from any suitable material. In the exemplary
14 embodiment illustrated in the Figures, all components of the swatter 10 may be formed of
15 conventional molded plastic. Plastic is preferred for the trigger 24 since the integral return
16 spring 26 may be formed of suitably thin plastic for providing an effective elastic return force
17 for the trigger 24. In other embodiments, the rod 12 and handgrip 14 may be formed of wood
18 or metal as desired.

19 [0051] Although the swatter 10 is illustrated in the Figures as being in the form of a long
20 barreled pistol, it may take any suitable form including that of a rifle or other analogous
21 shooting implement so that the stretched lash 18 may be suitably aimed at the insect 16 within
22 an effective striking range R thereof for ensuring undetected swatting thereof.

23 [0052] As indicated above, continued development of the insect swatter has uncovered
24 problems in optimizing the exemplary rubber band used for the lash. If the lash is too short or
25 too stiff, the effective striking range is too small, and the ability to swat insects is impaired.

26 [0053] If the lash is too long or too resilient, the striking range may be extended, but at the
27 expense of the ability to impart sufficient energy for the whipping action and striking
28 effectiveness.

29 [0054] Accordingly, Figures 5 and 6 illustrate another embodiment of the insect swatter
30 which is identical to the embodiment shown in Figures 1-4, except for the introduction of an

1 improved duplex elastic lash 34 replacing the single elastic lash 18. The lash 34 includes a
2 pair of annular rubber bands 36,38 joined together at a knot 40 therebetween collectively
3 forming a unitary assembly.

4 **[0055]** The individual rubber bands 36,38 may have any conventional composition, and are
5 preferably standard rubber bands commercially available at common stationery supply stores.
6 In this way, the bands need not be custom made to size, cross section, and material
7 composition for the specifically sized rod 12, which reduces cost thereof; and makes
8 replacement bands readily available.

9 **[0056]** In the preferred embodiment, the two bands 36,38 are identical in size, cross section,
10 and material composition, and have equal lengths to position the knot midway between both
11 the nominal, unstretched combined length thereof, and the cocked length shown in Figure 6.

12 **[0057]** The two bands 36,38 are shown being assembled together in Figure 5, with the first
13 band 36 being intertwined in the second band 38 to form a conventional square knot
14 therebetween. By stretching apart the two bands, the size of the knot is automatically reduced
15 to about the size of the cross section of the two bands together. The resulting lash 34 therefore
16 has the general appearance of a figure-8, with the knot 40 being at the middle thereof.

17 **[0058]** The duplex lash 34 illustrated in Figures 5 and 6 may be directly substituted for the
18 single lash 18 illustrated in Figures 1-4, and is usable in the same manner as described above.
19 The only difference in configuration is the introduction of the knot 40 at junction of the two
20 bands; and the method of operation remains the same.

21 **[0059]** The bands 36,38 may have a standard size such as being about 9 cm long with a
22 rectangular cross section of about 1.6 mm by 3.2 mm. The combined length of the knotted
23 bands is about 18 cm, which is about the same as the 17 cm length of the exemplary single
24 lash 18. And, both the original lash 18 and the duplex lash 34 are stretchable to about 60 cm,
25 but with correspondingly different stiffnesses which affects their whipping performance.

26 **[0060]** As shown in Figure 6, compared with Figure 2, the first band 36 includes the distal
27 end 18a of the combined lash 34, which forms the first loop disposed through the keyhole.
28 The second band 38 includes the proximal end 18b of the combined lash 34, which forms the
29 second loop positionable around the latch 20 for being retained thereby. When the lash 34 is
30 stretched to the cocking position, the knot 40 is positioned atop the rod 12 and is readily

1 propelled forwardly with the two bands without obstruction by the rod itself.

2 [0061] The relatively small first band 36 terminating in the knot 40 uses the rod itself for
3 guidance during swatting, and the second band 38 follows the travel of the knot 40 from
4 which it extends. The duplex lash therefore enjoys accuracy of direction or firing, without the
5 knot 40 providing any obstruction in travel.

6 [0062] A particular advantage of the two bands joined together is their improved
7 cooperation not available in individual bands alone, irrespective of size. Each rubber band is a
8 spring having a respective spring constant or stiffness. By joining together in series end-to-
9 end the two bands 36,38, the resulting spring constant or stiffness thereof is the reciprocal of
10 the sum of the reciprocals of the individual stiffnesses. In other words for identical rubber
11 bands 36,38 joined in series, the combined stiffness thereof is one-half the stiffness of either
12 band.

13 [0063] Accordingly, the combined two bands 36,38 enjoy double their individual lengths,
14 yet with half the spring rate or stiffness of each band. The two bands can also be stretched to
15 double the stretching length of each band alone.

16 [0064] When the duplex lash 34 is assembled with the insect swatter 10 as shown in Figure
17 6, the large cocked length is readily achieved, without excessive stretching or stiffness. It
18 would be impossible to stretch a single band 36 or 38 to the large cocking length, and the
19 striking range of such single band would be severely limited.

20 [0065] Each of the two bands 36,38 may be stretched to substantially its maximum
21 capability, with the combined stiffness thereof being half that of each band alone. The
22 inherent resilience or elasticity of each of the bands combines upon firing of the swatter. The
23 initially stretched bands contract spontaneously as they are hurled forward by the potential
24 energy stored therein corresponding to the respective stiffness thereof, and the whipping
25 reaction re-stretches the bands in the forward direction for achieving a large striking range,
26 with substantial impacting energy. The striking range is therefore extended due to the half
27 stiffness of the combined bands.

28 [0066] Accordingly, the joining together of the two bands in a string improves performance
29 of the insect swatter, not possible by an individual band alone; nor possible with two bands
30 joined together in parallel. The combined stiffness of two bands in parallel is twice that of the

1 individual bands, and without increased striking range; and does not enjoy the benefits of the
2 differently operating series bands.

3 [0067] Although two identical bands are preferred, it is contemplated that two differently
4 sized bands could be used to advantage in forming the resulting duplex lash. And, it is also
5 contemplated that three or more bands could be joined together in series, if desired.

6 [0068] An additional advantage of using multiple bands in series is that the individual bands
7 could be formed differently from each other to have different size, cross section, and material
8 composition.

9 [0069] Development testing of the duplex lash configuration supports its extraordinary
10 effectiveness in swatting and killing ordinary house flies, typically with one shot due to the
11 easy aiming of the device. The use of the trigger adds aiming accuracy and spontaneity to the
12 firing process not available in the manual firing of the lash without the trigger.

13 [0070] The enhanced striking range of the series bands improves effectiveness of the
14 swatter, with a suitable amount of stiffness in the two bands for whipping the lash and
15 imparting commensurate swatting energy even for the biggest of ordinary house flies.

16 [0071] And, the use of ubiquitous rubber bands eliminates the need for special size lashes or
17 custom order lashes, and permits acceptable swatter performance by the simple knotting
18 together of two ordinary rubber bands.

19 [0072] While there have been described herein what are considered to be preferred and
20 exemplary embodiments of the present invention, other modifications of the invention shall be
21 apparent to those skilled in the art from the teachings herein, and it is, therefore, desired to be
22 secured in the appended claims all such modifications as fall within the true spirit and scope of
23 the invention.

24 [0073] Accordingly, what is desired to be secured by Letters Patent of the United States is
25 the invention as defined and differentiated in the following claims, in which I claim: